## SCANDIC'S ACCESSIBILITY STANDARD

Here you can read our 110 point accessibility standard. It has been drawn up by carefully following the route taken by guests from the car park on through the whole hotel. We have also talked to disability organisations and guests with physical disabilities and received lots of ideas from our own keen staff. Although we rent our hotels rather than owning them, there is a lot that we can do. 81 of the 110 points are compulsory for all hotels. All 110 of the points need to be applied as we renovate or build new hotels.

The standard applies in all nine of the countries in which Scandic is represented. Of course we also have to comply with the legislation in the country concerned. This means that if the legislation in the country in question is stricter on any particular point, that takes precedence. In the cases where our standard is higher than the legislation, of course our standard applies.

Our accessibility standard doesn't include everything that we actually do on the ground. Accessibility issues are incorporated as part of our day to day work, whatever the area. This means that for example, safety issues involving accessibility are in our safety standard, signs in our signage standard, and so on. In other words accessibility issues are an important part of the whole of Scandic and everyone in our team undergoes training in them.

We describe the accessibility for each individual hotel on their respective websites. We are the only hotel chain in the world to do this.

/Magnus Berglund, disability ambassador Scandic Hotels

Number		Guest need/expectations	Mandatory	When reconstructing New building	Remarks	
PARK	ING &	ENTRANCE				
1		Accessible parking, ideally 2 spaces, each at least 3.6 metres wide.	Χ		If there is a car park	
2		Accessible parking must be clearly marked with the wheelchair symbol.	Χ			
3		Additional signage adjacent to bays " For help or assistance, call reception.	Χ			
4		Clear illuminated and delineated path between parking and entrance.	Χ		Wheelchair accessible	
5		Access ramps at change of level, with maximum slope gradient of 1:12, at main entrance to the hotel and the parking location.	Х			
6		Main entrance door to have a minimum width of 800 mm clear.	Χ			
7		Low or no threshold at the entrance door.	Χ			
8		Night time door bell accessible from wheelchair. With sign and illuminated.	Χ		Height 1200 mm	
9		Door openable with "automatic push plate", height 1200 mm.	Χ		If not automatic	
10		Clearly signed directions if the accessible entrance is not at the hotel's main entrance/building.	Χ			
11		Distance to entrance recommended maximum of 25 meters.		Χ		
12		Contrast markings – used in all public indoor areas.		Χ		
RECE	RECEPTION DESK					
13		Cane holders attached to front of desk, minimum 2.	Χ			
14		Seating and table available close to front desk so that guests may sit down at registration.	Χ			
15		Hearing loop in reception desk.	Χ		Marked with symbol sign	
16		Vibrating wake up/fire alarm device available to borrow.	Χ		Clearly signed on desk	



Number	Guest need/expectations	Mandatory	When reconstructing New building	Remarks
RECEPTION	N DESK			
17	Contrasting colour of rug leading from entrance door to the reception desk.		Х	
18 🗌	One part of the counter with appropriate height for guests in wheel chairs.		Х	
LOBBY				
19	Reachable electrical socket for charging electric wheelchairs. Height 1200 mm.		Х	
20	Shop – clear aisles at least 800 mm wide. Goods reachable from a wheelchair.	Х		
21	Clear walkway between reception and lifts (and other public areas).	Х		
22 🗌	Seating should be provided close to the main entrance.	Χ		Waiting for taxi area
EASY ACCE				
23	Minimum one work station that is accessible for a wheel chair.	Х		
24	One "standing up" work station.		Х	
ELEVATOR				16
25	(Clearly visible directional signage to the accessible elevator).	X		If not all are
26	Door opener (if not automatic).		Х	
27 📙	Elevator button and control panel accessible from a wheelchair.	Х		
28	Control panel buttons marked in Braille within lift and at each floor level.	Х		
29	Voice annunciation for floor indication and direction of travel.	Х		
30	Minimum one elevator with a minimum door width of 800 mm clear.	Х		
MAIN STAIL	RS (AND STAIRS BETWEEN FLOOR LEVELS)			
31 📙	First and last steps to be clearly marked in contrasting colours.	Х		Landings + 1/2 landings
32	Hand rails on both sides (if stairs wider than 1050 mm).	Х		
33	Hand rail to both start and finish 300 mm on either side of the stairs.		Х	
34	Stone or concrete stairs to have none slip finish on treds or nosings.		Х	
CLOAKROO	DM (WARDROBE)			
35	Clothes hangers or coat hooks reachable from a wheelchair, height 1200 mm.	Х		
	S (PATHS, WALKWAYS )  Corridors to be a minimum of 1300 mm clear width.	v		
36	Other indoor walkways, minimum of 800 mm clear width.	X	v	Between wall & pillar
37 L	• •		Х	DELWEETT WAIT & PHILA
38	Doors minimum of 800 mm clear width.		Х	
39	Minimum of one room with hard flooring.	Χ		For allergy suffers
	Telephones accessible from wheelchairs.	X		
40	Clothes hangers or coat hooks reachable from a wheelchair, height 1200 mm.	^	Х	
41 📙	Hearing loop available to borrow for conferences.	v	^	
42 📙		X		
43 📙	Sign stating that there is a hearing loop for conferences.	Х		



Number		Guest need/expectations	Mandatory	When reconstructing New building	Remarks
AUD	ITORIU	М			
44		Stage – wheelchair accessible.	Χ		Max ramp slope < 1:12
45		Podium - alternative with wheelchair accessibility available.		Х	
46		Audience wheelchair space available with easy access.	Χ		
47		No door thresholds.		Х	
BREA	ak ou	Γ AREAS			
48		Seating available outside meeting rooms.	Χ		
F&B	OUTLE				
49		Buffées, hight between 850-900 mm.		Х	
50		Coffee cups and glasses reachable from a wheelchair.	Χ		
51		Breakfast – special bread for people with a gluten or lactose intolerance.	Х		
ACC	ESSIBI	LITY GUEST BATHROOMS			
52		Signs showing where the accessibility toilet is located.	Х		
53		Passage in door minimum 800 mm.	Χ		900 mm recommended
54		Handrail on the inside of the door under the handle.	Χ		
55		No threshold (ground beam).	Χ		
56		Alarm.	Х		According to Scandic Safety&Security Manual
57		Mirror to be placed in an appropriate height (wheelchair).	Х		
WAS	SH BAS	IN AREA			
58		Wash basin minimum height 780 mm.	Χ		
59		Space under wash basin accessible for wheelchairs.	Χ		
60		Single lever basin mixer.	Χ		
61		One soap dispenser standard model "Squeeze" reachable from wheelchair.	Х		
62		One soap dispenser "special accessible range", reachable from wheelchair.	Х		
63		Towels reachable from wheelchair.	Х		
64		Hooks for jackets reachable from wheelchair ( height 1200 mm).	Χ		
65		Walking stick holder, x1 at a height of 1200 mm.		Х	
	ET AR	EA			
66		Foldable armrests.	Χ		
67		Toilet paper holder on armrest.	Χ		
DIRE	CTION	AL SIGNAGE			
68		Clearly marked in contrasting colour.	Χ		
69		Placed on height 1400-1600 mm.		Х	
SLEE	EPING	- ACCESSIBILITY GUEST ROOM			
70		Telephone hand set on side table.	Χ		
71		TV remote control placed on side table.	Χ		
72		Bed – height-adjustable for back and legs.		Х	



Number	Guest need/expectations	Mandatory	When reconstructing New building	Remarks			
73	Bed height 550 mm, recomended.	Х		Height of total bed incl. top mattress			
74	Minimum 800 mm free floor space on 1 side of the bed.	Х					
75	Minimum 800 mm free floor space around the bed.		Х	On 3 sides of the bed			
OTHER - A	OTHER - ACCESSIBILITY GUEST ROOM						
76	Two peepholes in the door, one at the usual height and one at 1200 mm.		Х				
77	Passage in main entrance minimum 800 mm.	Χ					
78	Wardrobe without doors or with sliding doors.	Χ					
79	Rail for coathanger height 1200 mm.	Χ					
80	Wardrobe shelf accessible from wheelchair.	Χ					
81 🗌	Blackout in room must be accessible from a wheelchair.		Χ				
82 🗌	Desk – wheelchair accessible.	Χ					
83	Electrical socket at the desk reachable from a wheelchair.		Х				
84	Wardrobe with sliding door or no door.		Χ				
BATHROOM	1 - ACCESSIBILITY GUEST ROOM						
85	Passage in door minimum 800 mm.	Χ					
86	Handrail on the inside of the door under door opener.	Х					
87	No threshold (ground beam).	Χ					
88	Alarm.	Х		According to Scandic Safety&Security Manual			
89 🗌	Sliding door.	Х		Recommendation for renovations and newly built hotels			
90	Wash basin minimum height 780 mm.	Х					
91	Space under wash basin accessible for wheelchairs.	Χ					
92	Single lever basin mixer.	Χ					
93	One soap dispenser standard model "Squeeze" reachable from a wheelchair.	Χ					
94	One soap dispenser "special disable range", reachable from a wheelchair.	Χ					
95	Towels reachable from wheelchair.	Χ					
96	Hooks reachable from wheelchair ( height 1200 mm).	Χ					
97	Vanity mirror reachable from a wheelchair.	Χ					
98	Hairdryer reachable from a wheelchair.	Х					
SHOWER A	REA						
99	Wheelchair accessible.	Χ					
100	Thermostatic mixer.	Χ					
101	One shower creme/shampoo dispenser standard model "Squeze" reachable from a wheelchair.	Х					
102	Shelf (height max 1200 mm) for e.g. shampoo.	Х					
103	Shower chair avaible.	Х					
104	Shower chair with back and arms compulsory when purchasing new.		Χ				
105	Towels reachable from wheelchair.	Х					



Number	Guest need/expectations	Mandatory	When reconstructing New building	Remarks		
106	Showerhandle placed in its lowest when guest arrives.	Χ				
107	Shower curtain or shower glass wall.		Χ	To be faced out		
108	Shower glass wall.	Х	Х	To be in new built, refurbishment and replacement		
TOILET AREA						
109	Foldable armrests.	Χ				
110	Toiletpaper holder on armrest.	Χ				









